

Safety, Easy operation, Speedy pigments change Rotation type Pellet Sorter & Wax Blender

*Best combination
of pellet finishing*

Rotation type Pellet Sorter



By adopting of a rotation type, generation of the static electricity which is the risk of an oscillating type sorter was controlled. End powder is discarded without adhering to a pellet.

The KPL type is the specification which lengthened the KP type mesh portion (end powder removal portion).

Special order manufacture of the punching drum diameter 400 specification (for 500kg processing) is carried out.

Specification	Model	KP-400	KP-600	KPL-400	KPL-600
Drum size (mm)		Mesh 400 / Punching 400	Mesh 400 / Punching 600	Mesh 600 / Punching 400	Mesh 600 / Punching 600
Production Ability		200kg/Hour	300kg/Hour	200kg/Hour	300kg/Hour
Drive Motor		0.4kW Geared Motor			
Drive Control		Inverter			
Mesh		Diameter: 300 #8, #9, #12 Long hole punching: 1.5x15, 2x10, (Order made specification is available)			
Punching		Diameter: 300 Hole diameter: 4, 5, 6, 7, 8, (Order made specification is available)			

Wax Blender

This wax blender is equipment which controls the number of rotations of a variable speed motor by a dial gauge, and adjusts the amount of supply of wax. Fine tuning of the wax amount of supply is easy, and the processing when getting wax blocked is easy.

Capacity	3 liters
Rotative Velocity	0 ~ 2.3 r.p.m.



KATSUMIX CO., LTD.

5043-8 Kimagase, Noda-city, Chiba 270-0222, JAPAN

Phone: 04-7198-2171 Fax: 04-7198-0834

e-mail: e-mix@katsumix.com URL: <http://www.katsumix.com>